

| | Standard | Result |
|---------------------------------|---|---|
| Thickness | | 3.0 mm |
| Size | | See separate table |
| Wear layer | | 30 mil ¹ (0.7 mm) |
| Surface treatment | | K-Guard+® PU coating |
| Warranty ² | Commercial Residential | 20 Years Lifetime |
| Beveled Edge | | Standard |
| Classification | ASTM F1700 | Class III Type B |
| Reaction to fire | ASTM E648-06 | Class 1 |
| Smoke density | ASTM E662-06 | Pass (< 450) |
| Flammability test | FF 1-70; Federal Approval | Pass |
| Slip resistance ³ | ASTM D2047 | Pass (Dry 0.92) |
| Staining resistance | ASTM F925 | Pass |
| Light fastness | ASTM F1515 | Pass $\Delta E = 3.3$ |
| Abrasion resistance | ASTM D3884 | 115,000 Cycles |
| Dimensional stability | ASTM F2199 | Pass -0.002"/lin.ft |
| Acoustic impact noise reduction | ASTM E2179-09 ASTM E492-09 | $\Delta IIC = 6$ dB IIC = 46 dB (6" Concrete Slab w/Drop Ceiling) IIC = 71 dB (6" Concrete Slab w/Drop Ceiling + QuietChoice) |
| Static load | ASTM F970 | 1,000 psi |
| Flexibility | ASTM F137 | Pass |
| Adhesive | | K-Spray K99 HM Karndean DrySet 2-Part Epoxy Resin |
| Environmental | FloorScore® SCS-EC10.3-2014 v4.0 Environmental Product Declaration NSF / ANSI 332 ISO 14001 / ISO 9001 | Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards |
| Recycling | | Suitable |
| Phthalate free | | Yes |

¹Nominal

²Subject to terms

³Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Call: 866-819-6825

Email: info@karndeancanada.ca

Visit: www.karndean.com



| | Product Code | Size | | Box Quantity | |
|--------------|---------------|-----------|---------------|-----------------|-----------|
| | | inches | mm | ft ² | Pieces |
| Wood Designs | RP41 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP61 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP73 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP91 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP94 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP95 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP96 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP98 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP99 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP100 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP101 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP102 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP103 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | RP105 | 36" x 3" | 914.4 x 76.2 | 36.00 | 48 Planks |
| | Stone Designs | CER12 | 12" x 18" | 304.8 x 457.2 | 36.00 |
| CER13 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |
| CER14 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |
| CER16 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |
| CER17 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |
| CER19 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |
| CER20 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |
| CER21 | | 12" x 18" | 304.8 x 457.2 | 36.00 | 24 Tiles |