Coral Brush Activ
Technial Data

Karndean Designflooring

	Standard	Result
Type of manufacture		Tufted, 5/32" cut pile
Width		200cms (roll length 27.5M)
Design/colour		Multi coloured designed/coloured
Pile material		100% polyamide
Primary Backing		Non-woven polyester
Backing		Everfort ® vinyl
Pile Weight		Approx. 920 g/m²
Pile density	ISO 8543	Approx. 0.106 g/cm³
Pile thickness	ISO 1766	Approx. 7.0mm
Total weight	ISO 8543	Approx. 3700 g/m²
Total thickness	ISO 1765	Approx. 10 mm
Number of tufts per m2	ISO 1763	Approx. 68,000
Wear classification	EN 1307	Class 4 Heavy Commercial
Comfort classification	EN 1307	Class 3
Antistatic	EN 1815	< 2 kV (antistatic)
Electrical vertical resistance	ISO/DIS 10965	Approx. 1011 Ω
Acoustic insulation	ISO 140-8	Δ Lw= 37 dB
Acoustic absorption	ISO 354	Freq. Hz. 125 250 500 1000 2000 4000 as 0.02 0.07 0.13 0.33 0.45 0.57
Thermal resistance	ISO 8302	0.18 m² K/W
Colour fastness to		
Rubbing	ISO 105 X12	5
Water	ISO 105 E01	5
Light	ISO 105 B02	7
Sea water	ISO 105 E02	4
Organic solvents	ISO 105 X05	4-5
Shampoo	BS 1006	4
Chlorinated water	ISO105	1
Slip Resistance	AS/NZS 4586–1999	Oil wet ramp: Class R12
Fire resistance	BS4790: 1972 AS/ISO 9239.1–2003 ASTM E648-91a	Class low radius CHF value: 5.7 kW/m². Smoke value: 594%min. Class 1

For more information:

Australia
Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndean.com.au

New Zealand
Call: 0800 44 21 01
Email: customerservice@karndean.co.nz
Visit: www.karndean.co.nz

coral® brush activ

breathe Easy

Your space. Your needs. **Your style.**