



Technical Data



			Slip Resistance			
	Standard	Result	Product	Size (mm)	Oil-Wet Ramp	Wet Pendulum
Size		See separate table	VG 1-7	1219 X 178	R10	Y
Thickness		3.0 mm	VG 5-7	1219 X 178	R10	Y
Wear Layer		0.5 mm	VGW33T-7	1219 X 178	R10	Y
Warranty	Commercial	10 years*	VGW39T-7	1219 X 178	R11	W
	Domestic	15 years*	VGW40T-7	1219 X 178	R10	Y
Bevelled Edge		No	VGW41T-7	1219 X 178	R11	W
Standards	EN 649	Pass	VGW42T-7	1219 X 178	R11	W
	ASTM F1700	Pass	VGW44T-7	1219 X 178	R11	W
Classification		Commercial Heavy Duty use	VGW49T-7	1219 X 178	R11	W
		Domestic Heavy Duty use	VGW53T-7	1219 X 178	R11	W
Staining Resistance	EN 423	Class 0	VGW54T-7	1219 X 178	R11	W
	ASTM F925	Pass	VGW70T-7	1219 X 178	R11	W
Colour Fastness to Light	ISO 105-B02	≥7	VGW71T-7	1219 X 178	R11	W
	ASTM F1515	<8	VGW80T-7	1219 X 178	R11	W
Abrasion Resistance	EN 660-2	Group T	VGW81T-7	1219 X 178	R11	W
	ASTM D3884	Pass	VGW83T-7	1219 X 178	R11	W
Dimensional stability	EN 434	≤ 0.25%	VGW84T-7	1219 X 178	R11	W
	ASTM F2199	Pass	VGW86T-7	1219 X 178	R11	W
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 4 db ¹	VGW87T-7	1219 X 178	R11	W
Electrical behaviour body voltage	EN 1815	Pass	VGW88T-7	1219 X 178	R11	W
Indentation - residual	EN 433	≤ 0.1mm	VGW89T-7	1219 X 178	R11	W
	ASTM F1914	<8%				
Castor chair continuous use	EN 425	Pass				
Thermal conductivity	ISO 8302	0.0147 m ² K/W				
		Suitable for underfloor heating				
Reaction to Fire	AS NZS ISO 9239.1:2003	CRF: 9.4 kW/m ²				
		Smoke value: 84% min.				
Slip resistance	AS/NZS 4586:2004	See separate table				
Adhesive	General use:	Karndean Mega-Bond				
	High temperature:	Karndean 8000 2-part Polyurethane				
Recycling		Suitable				

*Subject to terms

¹Result is Ln,w + C¹ = 57 dB when installed on Regupol 4515 acoustic underlay

For more information:

Australia

Call: 1800 33 11 70

Email: customerservice@karndean.com.au

Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.com



green building council australia
MEMBER 2013-2014

