




Technical Data



	Standard	Result
Size	ISO 24342	See separate table
Thickness	ISO 24346	2.0 mm
Wear Layer		0.3 mm
Surface treatment		K-Guard+ PU coating
Warranty	Commercial	10 years light commercial*
	Domestic	Lifetime wear*
Bevelled Edge		No
Standards	EN 649/EN ISO 10582	Pass
	ASTM F1700	Pass
Classification		Commercial Light Duty use Domestic Heavy Duty use
Staining Resistance	EN ISO 26987/EN 423	Excellent
	ASTM F925	Pass
Colour Fastness to Light	ISO 105-B02	≥6
	ASTM F1515	<8
Abrasion Resistance	EN 660-2	Group T
	ISO 10582	Type 1
	ASTM D3884	Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ ISO 23999	≤ 0.25%
	ASTM F2199	Pass
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 1 Db**
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ ISO 24343-1	≤ 0.1mm
	ASTM F1914	<8%
Castor chair continuous use	EN 425/ ISO 4918	Pass
Thermal resistance	ISO 8302	0.0100 m ² K/W Suitable for underfloor heating
Reaction to Fire	AS/NZS ISO 9239.1:2010	CRF: 8.1 kW/m ² Smoke value: 42% min.
***Slip resistance	AS/NZS 4586:2013	See separate table
Adhesive	General use:	Karndean Mega-Bond
	High temperature:	Karndean 8000 2-part Polyurethane
Recycling		Suitable
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level'A';LCA Silver Plus; Best Practice PVC
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
Phthalate free		Yes

Product	Size (mm)	Slip Resistance Oil-Wet Ramp
KP37	914.4 X 101.6	R9
KP39	914.4 X 101.6	R9
KP54-6	914.4 X 152.4	R10
KP55-6	914.4 X 152.4	R10
KP91	914.4 X 101.6	R9
KP94	914.4 X 152.4	R10
KP95	914.4 X 152.4	R10
KP96	914.4 X 152.4	R10
KP97	914.4 X 152.4	R10
KP98	914.4 X 152.4	R10
KP101	914.4 X 152.4	R10
KP103	914.4 X 152.4	R10
KP104	914.4 X 152.4	R10
KP107	914.4 X 101.6	R9
KP131	914.4 X 152.4	R10
KP136	914.4 X 152.4	R10
KP137	914.4 X 152.4	R10
KP138	914.4 X 152.4	R10
KP139	914.4 X 152.4	R10
KP141	914.4 X 152.4	R10
KP142	914.4 X 152.4	R10
ST5-18	457.2 X 304.8	R9
ST8	304.8 X 304.8	R9
ST9	304.8 X 304.8	R9
ST11	457.2 X 304.8	R9
ST12	457.2 X 304.8	R9
ST13	457.2 X 304.8	R9
ST14	457.2 X 304.8	R9
ST16	457.2 X 304.8	R9
T88	304.8 X 304.8	R9
T89	304.8 X 304.8	R9
T98	304.8 X 304.8	R9
T99-18	457.2 X 304.8	R9
T100	304.8 X 304.8	R9

*Subject to terms

**Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay

***Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:

Australia

Call: 1800 33 11 70

Email: customerservice@karndean.com.au

Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.com

