



# Technical Data



	Standard	Result	Product	Size (mm)	Slip Resistance Oil-Wet Ramp
Size	ISO 24342	See separate table	SP111	457.2 X 457.2	R10
Thickness	ISO 24346	2.5 mm	SP112	457.2 X 457.2	R10
Wear Layer		0.5 mm	SP113	457.2 X 457.2	R10
Surface treatment		K-Guard+ PU coating	SP114	457.2 X 457.2	R10
Warranty	Commercial	15 years wear*	SP115	457.2 X 457.2	R10
	Domestic	Lifetime wear*	SP211	609.6 X 457.2	R10
Bevelled Edge		No	SP212	609.6 X 457.2	R10
Standards	ASTM F1700	Pass	SP213	609.6 X 457.2	R10
Classification		Commercial Heavy Duty use	SP214	609.6 X 457.2	R10
		Domestic Extra Heavy Duty use	SP215	609.6 X 457.2	R10
Staining Resistance	EN ISO 26987/EN 423	Excellent	SP216	609.6 X 457.2	R10
	ASTM F925	Pass	SP217	609.6 X 457.2	R10
Colour Fastness to Light	ISO 105-B02	≥7	WP311	914.4 X 152.4	R10
	ASTM F1515	<8	WP312	914.4 X 152.4	R10
Abrasion Resistance	EN 660-2	Group T	WP313	914.4 X 152.4	R10
	ISO 10582	Type 1	WP314	914.4 X 152.4	R10
	ASTM D3884	Pass	WP315	914.4 X 152.4	R10
Flexibility	ISO 24344	Pass	WP316	914.4 X 152.4	R10
Dimensional stability	EN 434/ ISO 23999	≤ 0.25%	WP317	914.4 X 152.4	R10
	ASTM F2199	Pass	WP318	914.4 X 152.4	R10
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 2 dB**	WP319	914.4 X 152.4	R10
Electrical behaviour body voltage	EN 1815	Pass	WP329	914.4 X 152.4	R10
Indentation - residual	EN 433/ ISO 24343-1	≤ 0.1mm	WP411	1219.2 X 228.6	R10
	ASTM F1914	<8%	WP412	1219.2 X 228.6	R10
Castor chair continuous use	EN 425/ ISO 4918	Pass	WP413	1219.2 X 228.6	R10
Thermal resistance	ISO 8302	0.0120 m <sup>2</sup> K/W	WP414	1219.2 X 228.6	R10
		Suitable for underfloor heating	WP421	1219.2 X 228.6	R10
Reaction to Fire	AS/NZS 9239.1:2010	CRF: >11 kW/m <sup>2</sup>	WP422	1219.2 X 228.6	R10
		Smoke value: 93% min.	WP423	1219.2 X 228.6	R10
***Slip resistance	AS/NZS 4586:2013	See separate table	WP511	914.4 X 101.6	R10
Adhesive	General use:	Karndean Mega-Bond			
	High temperature:	Karndean 8000 2-part Polyurethane			
Recycling		Suitable			
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level'A';LCA Silver Plus; Best Practice PVC			
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.			
Phthalate free		Yes			

\*Subject to terms

\*\*Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay

\*\*\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

### For more information:

#### Australia

Call: 1800 33 11 70

Email: [customerservice@karndean.com.au](mailto:customerservice@karndean.com.au)

Visit: [www.karndean.com](http://www.karndean.com)

#### New Zealand

Call: 0800 44 21 01

Email: [customerservice@karndean.co.nz](mailto:customerservice@karndean.co.nz)

Visit: [www.karndean.com](http://www.karndean.com)

Manufactured to ISO9001

