















# Technical Data



	Standard	Result
 Size	ISO 24342	1219.2 mm X 177.8 mm
 Thickness	ISO 24346	3.0 mm
 Wear Layer		0.5 mm
 Surface treatment		K-Guard+ PU coating
 Warranty	Commercial	15 years wear*
	Domestic	Lifetime wear*
 Bevelled Edge		No
 Standards	ASTM F1700	Pass
 Classification		Commercial Heavy Duty use Domestic Extra Heavy Duty use
 Staining Resistance	EN ISO 26987/EN 423	Excellent
	ASTM F925	Pass
 Colour Fastness to Light	ISO 105-B02	≥7
	ASTM F1515	<8
 Abrasion Resistance	EN 660-2	Group T
	ISO 10582	Type 1
	ASTM D3884	Pass
 Flexibility	ISO 24344	Pass
 Dimensional stability	EN 434/ISO 23999	≤ 0.25%
	ASTM F2199	Pass
 Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 4 dB**
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN 433/ISO 24343-1	≤ 0.1mm
	ASTM F1914	<8%
 Castor chair continuous use	EN 425	Pass
 Thermal conductivity	ISO 8302	0.0147 m <sup>2</sup> K/W Suitable for underfloor heating
 Reaction to Fire	AS/NZS 9239.1:2010	CRF: 7.3 kW/m <sup>2</sup> Smoke value: 124% min.
 ***Slip resistance	AS/NZS 4586:2013	Oil-Wet Ramp: R10
 Adhesive	General use:	Karndean Mega-Bond
	High temperature:	Karndean 8000 2-part Polyurethane
 Recycling		Suitable
 Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level 'A'; LCA Silver Plus; Best Practice PVC
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
 Phthalate free		Yes

\*Subject to terms

\*\*Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay

\*\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:

**Australia**

Call: 1800 33 11 70

Email: customerservice@karndean.com

Visit: www.karndean.com

Manufactured to ISO9001

