



Technical Data

	Standard	Result
Thickness		3.0 mm (1/8")
Size		48" x 7"
Wear layer		20 mil (0.50 mm)
Surface treatment		K-Guard+ PU coating
Warranty*	Commercial	15 years
	Residential	Lifetime
Beveled edge		Micro
Classification	ASTM F1700	Class III Type B
Reaction to fire	ASTM E648-06	Class 1
Smoke density	ASTM E662-06	Pass (<450)
Flammability test	FF 1-70; Federal Approval	Pass
Slip resistance**	ASTM D2047	Pass (Dry 0.89)
Staining resistance	ASTM F925	Pass
Light fastness	ASTM F1515	Pass $\Delta E = 3.3$
Abrasion resistance	ASTM D3884	115,000 cycles
Dimensional stability	ASTM F2199	Pass -0.002"/lin.ft
Acoustic Impact noise reduction	ASTM E2179-09 ASTM E492-09	$\Delta IIC = 6$ dB IIC= 46 dB (6"slab w/drop ceiling) IIC= 71 dB (6"slab w/drop ceiling+Quiet choice)
Static load	ASTM F970	1,000 psi
Flexibility	ASTM F137	Pass
Adhesive		K-91AR DrySet K-Spray Karndean Epoxy
Recycling		Suitable
Phthalate free		Yes

*Subject to terms

**Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:

Call: 866-819-6825

Email: info@karndeancanada.ca

Visit: www.karndean.com

Manufactured to ISO9001

Size Box quantity

48" x 7" 15 Planks/35 ft²

