



Technical Data



| | Standard | Result | Product | Size (mm) | LRV |
|--|--|--|---------|-------------------------|-----|
| | EN ISO 24342 | See separate table | CC04 | 406.4 x 406.4 (16"x16") | 75 |
| | EN ISO 24346 | 3.0 mm | CC06 | 406.4 x 406.4 (16"x16") | 14 |
| | EN ISO 24340 | 0.7 mm | CER11 | 304.8 X 457.2(12"x18") | 11 |
| | | K-Guard+ PU coating | CER12 | 304.8 X 457.2(12"x18") | 9 |
| | EN ISO 23997 | 5015 g/m ² | CER13 | 304.8 X 457.2(12"x18") | 9 |
| | Light industrial | 20 years* | CER14 | 304.8 X 457.2(12"x18") | 9 |
| | Commercial | 20 years* | CER15 | 304.8 X 457.2(12"x18") | 35 |
| | Residential | Lifetime guarantee* | CER16 | 304.8 X 457.2(12"x18") | 21 |
| | | Standard | CER17 | 304.8 X 457.2(12"x18") | 21 |
| | EN 649/ ISO 10582 | Pass | CER18 | 304.8 X 457.2(12"x18") | 53 |
| | EN 685/ EN ISO 10874- Light industrial | 43: Light industrial heavy | CER19 | 304.8 X 457.2(12"x18") | 19 |
| | EN 685/EN ISO 10874- Commercial | 34: Commercial very heavy | CER20 | 304.8 X 457.2(12"x18") | 31 |
| | EN 685/EN ISO 10874- Domestic | 23: Domestic heavy | CER21 | 304.8 X 457.2(12"x18") | 12 |
| | EN 13501-1 | B _{fl} -s1 | CK25 | 406.4 x 406.4 (16"x16") | 8 |
| | EN ISO 26987/EN 423 | Excellent | LST02 | 406.4 x 406.4 (16"x16") | 53 |
| | EN ISO 105-B02 | ≥6 | LST03 | 406.4 x 406.4 (16"x16") | 49 |
| | EN 649 | Group T | LST04 | 406.4 x 406.4 (16"x16") | 40 |
| | EN ISO 10582 | Type 1 | LST05 | 406.4 x 406.4 (16"x16") | 26 |
| | EN ISO 24344 | Pass | RP11 | 914.4 X 76.2(36"x3") | 37 |
| | EN 434/ EN ISO 23999 | Pass | RP41 | 914.4 X 76.2(36"x3") | 8 |
| | EN ISO 717-2 / EN ISO 140-8 | ΔL _w = 2 dB | RP73 | 914.4 X 76.2(36"x3") | 20 |
| | EN 1815 | Pass | RP90 | 914.4 X 76.2(36"x3") | 25 |
| | EN 433/EN ISO 24343-1 | Pass ≤ 0.1mm | RP91 | 914.4 X 76.2(36"x3") | 17 |
| | EN 425/ ISO 4918 | Pass | RP92 | 914.4 X 76.2(36"x3") | 13 |
| | ISO 8302 | 0.0147 m ² K/W | RP94 | 914.4 X 76.2(36"x3") | 10 |
| | | Suitable for underfloor heating. Max 27°C | RP95 | 914.4 X 76.2(36"x3") | 12 |
| | DIN 51130 | R10 | RP96 | 914.4 X 76.2(36"x3") | 22 |
| | EN 13893 | DS | RP97 | 914.4 X 76.2(36"x3") | 19 |
| | BS 8493:2008+A1:2010 | See separate table | RP98 | 914.4 X 76.2(36"x3") | 25 |
| | ISO 16000 | Indoor Air Comfort Gold | RP99 | 914.4 X 76.2(36"x3") | 13 |
| | Karndean Universal | Yes | RP100 | 914.4 X 76.2(36"x3") | 17 |
| | Acrylic | Yes | RP101 | 914.4 X 76.2(36"x3") | 12 |
| | Epoxy | Yes | RP102 | 914.4 X 76.2(36"x3") | 28 |
| | High Temperature | Yes | RP103 | 914.4 X 76.2(36"x3") | 26 |
| | Pressure sensitive | Yes | RP104 | 914.4 X 76.2(36"x3") | 13 |
| | | Suitable | RP105 | 914.4 X 76.2(36"x3") | 9 |
| | | Yes | | | |

*Subject to terms. Please see our website.

** Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Call: 01386 820104

Email: commercial@karndean.co.uk

Visit: www.karndean.com

For ROI call: 01 6569887

Manufactured to ISO9001



EN 14041:2004 (DOP 2017/Mon/EN/01)
Notified body 0321
Floor Coverings (Internal)
ISO 10874 Class 23/34/43
Manufactured to ISO 10582

