



	Standard	Result	Product	LRV
	EN ISO 24342	1500 x 250 mm	LLP301	20
	EN ISO 24346	4.5 mm	LLP302	11
	EN ISO 24340	0.55 mm	LLP303	11
		K-Guard+ PU coating	LLP304	31
	Light industrial	15 years*	LLP305	20
	Commercial	15 years*	LLP306	40
	Residential	Lifetime guarantee*	LLP307	21
		No	LLP308	29
	EN ISO 23997	7470 g/m <sup>2</sup>	LLP310	31
	EN 649/ EN ISO 10582	Pass	LLP311	58
	EN 685/EN ISO 10874- Light industrial	42: Light industrial general	LLP315	14
	EN 685/EN ISO 10874- Commercial	33: Commercial heavy	LLP317	26
	EN 685/EN ISO 10874- Domestic	23: Domestic heavy		
	EN 13501-1	B <sub>f1</sub> -s1		
	EN ISO 26987/EN 423	Excellent		
	EN ISO 105-B02	≥7		
	EN 649	Group T		
	EN ISO 10582	Type 1		
	EN ISO 24344	Pass		
	EN 434/ EN ISO 23999	≤ 0.10%		
	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 13 dB		
	EN 433 EN ISO 24343-1	Pass ≤ 0.1mm		
	EN 425/ ISO 4918	Pass		
	ISO 8302	0.0245 m <sup>2</sup> K/W Suitable for underfloor heating. Max 27°C		
	DIN 51130	R10		
	EN 13893	DS		
	BS 8493:2008+A1:2010	See separate table		
	ISO 16000	Indoor Air Comfort Gold		
		Please refer to our installation instructions.		
		Suitable		
		Yes		

\*Subject to terms. Please see our website.

\*\* Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

**For more information:**

Call: 01386 820104

For ROI call: 01 6569887

Email: [commercial@karndean.co.uk](mailto:commercial@karndean.co.uk)

Visit: [www.karndean.com](http://www.karndean.com)

Manufactured to ISO9001



EN 14041:2004 (DOP 2017/LLLB/EN/01)
Notified body 0321
Floor Coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582

