

## Korlok Select Technical Data

	Standard	Result
Thickness	ASTM F386	6.5 mm
Size	ASTM F2421	See separate table
Locking system*		5G® short edge; 2G long edge
Wear layer	ASTM F410	20 mil (0.50 mm)
Surface treatment		K-Guard+ PU coating
Warranty***	Commercial	15 years
	Residential	Lifetime
Bevelled edge		Micro
Standards	ASTM F3261	Pass:-Resilient flooring with Rigid Polymeric Core
Reaction to fire	ASTM E648-06	Class 1
Flammability	ASTM D2859	Pass
Slip resistance****	ASTM D2047	Pass (Dry >0.8)
Staining resistance	ASTM F925	Pass (No change)
Heat Fastness	ASTM F1514	Pass
Light fastness	ASTM F1515	Pass
Electrostatic propensity	AATCC 134	1.6 kV
Abrasion resistance	ASTM D4060	Pass 36 000 cycles
Dimensional stability	ASTM F2199	Pass (-0.003"/lin.ft)
Static Load	ASTM F970	Pass 800 psi at 0.005"
Small ball impact	NALFA 3.6	Pass class 4
Large ball impact	NALFA 3.5	Pass class 4
Acoustic impact noise reduction	ASTM E2179-09	ΔIIC = 22 dB
	ASTM E492-09	IIC = 68 dB (6" Concrete Slab w/Drop Ceiling) IIC = 72 dB (6"slab w/drop ceiling+QuietChoice)
Indentation-residual	ASTM F 1914	Pass (2.3 %)
Thickness swell	NALFA 3.2	Pass class 4
Chair resistance	NALFA 3.9	Pass class 4
Surface bond	NALFA 3.10	Pass class 4
Thermal resistance	ISO 8302	0.052 m <sup>2</sup> K/W suitable for underfloor heating max 81 °F
Adhesive		None required; please install according to our installation instructions.
Recycling		Suitable
Phthalate free		Yes

Product	Size (inch)
RKP8101	55.91" x 8.86"
RKP8102	55.91" x 8.86"
RKP8103	55.91" x 8.86"
RKP8104	55.91" x 8.86"
RKP8105	55.91" x 8.86"
RKP8107	55.91" x 8.86"
RKP8108	55.91" x 8.86"
RKP8109	55.91" x 8.86"
RKP8110	55.91" x 8.86"
RKP8111	55.91" x 8.86"
RKP8114	55.91" x 8.86"
RKP8115	55.91" x 8.86"
RKP8116	55.91" x 8.86"
RKP8122	55.91" x 8.86"
RKP8124	55.91" x 8.86"
RKP8126	55.91" x 8.86"
RKP8202	55.91" x 8.86"
RKP8203	55.91" x 8.86"
RKP8206	55.91" x 8.86"
RKP8208	55.91" x 8.86"
RKP8209	55.91" x 8.86"
RKP8211	55.91" x 8.86"
RKP8215	55.91" x 8.86"
RKP8217	55.91" x 8.86"
SM-RKP8208	23.46" x 5.87"
SM-RKP8209	23.46" x 5.87"
SM-RKP8211	23.46" x 5.87"

Size	Box quantity
55.91" x 8.86"	10 planks/34.39 sq.ft
23.46" x 5.87"	22 planks/21.03 sq.ft

\*Produced under Licence from Valinge Innovations

\*\*5G short edge; 2G long edge except SM-RKP8208, SM-RKP8209, SM-RKP8211 which are modified 2G on short edge and standard 2G long edge

\*\*\*Subject to terms

\*\*\*\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained

For more information:

Call: 888-266-4343

Email: info@karndean.com

Visit: www.karndean.com