

Pedigree - Entrance Zone

Construction	Textile Entrance Matting
Pile material	Tufted Solution Dyed Nylon
Backing	Vinylback - PVC
Maintenance	Vacuum daily with a powerful rotating brush vacuum. Periodic cleaning with residue free hot water extraction.
Warranty	5 years

<u>Style</u>	<u>Grid</u>	<u>Weave</u>
Description	Multi-textured linear	Mottled semi plain
Scraper fibres	Yes	Yes
Pile weight	825 gram/m ²	850 gram/m ²
Total weight	3525 gram/m ²	3650 gram/m ²
Pile height	6 mm	7.5 mm
Total height	8 mm	9 mm
Roll width	200 cm, plus 2.5 cm edging on each side	195 cm, plus 2.5 cm edging on each side
Roll Length	20 m (approx)	20 m (approx)
Colours	4	6
	Standard	Result
Use classification	EN1307	Class 32 General use
Wearing class	EN1307	Class 32 General use
Suitability for stairs	EN1963	Intensive use
Suitability for castor chairs	EN985	Intensive use
Water absorption	TNO W6034	±5.3 litres/m ²
Light fastness	ISO 105 B02	>7 (scale 1-8)
Water fastness	ISO 105 E01	4-5 (scale 1-5)
Rubbing fastness	ISO 105 X12	4-5 (scale 1-5)
Reaction to fire	AS/NZS 9239.1	CRF : 4.71 kW/m ² Smoke release: 241%-minutes
Slip resistance	AS/NZS 4586-2004	Appendix A: Wet pendulum V Appendix D: Oil wet ramp R12

For more information:

Australia

Call: 1800 33 11 70

Email: customerservice@karndean.com.au

Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.com



green building council australia
MEMBER 2013-2014

