



Packaged in recycled,
EcoPure® treated,
biodegradable pail



Karndean
Designflooring



CERTIFIED BY
SCS Global Services

K-95HM

High Moisture 95% RH

Outstanding moisture resistance
up to 95%RH

High shear strength

pH up to 10.0

Ultra low odor

Karndean K-95HM is a premium high-strength adhesive for installing vinyl tiles and dimensionally stable vinyl plank in extreme moisture conditions. Karndean K-95HM can tolerate moisture as high as 95%RH providing there is no visible moisture or standing water. Read the Technical Data Sheet completely for uses and limitations before using this product. Karndean K-95HM is a solvent-free, acrylic adhesive suggested for use in occupied buildings, as it is low in odor, low VOC. Karndean K-95HM contains a broad spectrum antimicrobial to protect the adhesive from bacterial and fungal growth.

Substrate Preparation:

All substrate preparation and testing procedures must conform to appropriate ASTM F710 guidelines, and comply with Karndean's specifications.

NOTE: It is up to the end user to determine the coverage that is appropriate for flooring and jobsite conditions. Bond testing prior to the installation will help to identify the appropriate application rate, open and working time, and any potential bonding problems to the substrate or flooring.

Substrate Conditions:

Use on concrete substrates with up to 95% RH (per current ASTM F2170) and a MVER of up to 8 lbs. pH of 8.0-10.0.

Application:

Use a 1/16" x 1/32" x 1/32" U-notch trowel. The coverage will be approximately 220-260 square feet per gallon. Always roll the installation in both directions with a 75-100 lbs. 3-section roller immediately after flooring is placed and positioned, ensuring complete contact with the adhesive.

Porous or Non-porous Substrates:

LVT/LVP may be placed into adhesive on either porous or non-porous substrates once adhesive is "dry to the touch". When installing LVT/LVP over a non-porous substrate, drying time of the adhesive may vary depending on temperature, humidity, etc. Loss of adhesion can result if the flooring is not installed within the 2 hour working time of the adhesive.

Traffic:

Foot traffic and furniture replacement are immediate after installation and clean up. Heavy rolling load, Hill Rom hospital beds etc, can resume after 48 hours. Allow at least 5 days following the installation before conducting wet cleaning procedures or initial maintenance.

Clean-up:

Use a clean wet cloth to clean up adhesive while still wet. Dried adhesive may require the use of an appropriate solvent.

Limitations:

Do not allow product to freeze. Do not use on substrates that have been chemically cleaned or over treated plywood. Do not use to install vinyl-backed flooring over asphalt-based (cutback) adhesive residues. Read the Technical Data Sheet before using this product. This is a commercial adhesive and should only be used by professionals. Not labeled for Consumer use.

LEED® v4 Program Credits
(where applicable)

- IEQ Credit 4:
- Passes CA SCAQMD Rule 1168
- CA Section 01350 compliant

SAFETY INFORMATION:

Not a dangerous substance or mixture according to Hazardous Products Regulations (HPR) (SOR/2015-17)

FIRST AID MEASURES:

Inhalation: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not rub affected area. If eye irritation persists: Get medical advice/attention.

Skin contact: Wash off immediately with plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician.

Ingestion: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

DISPOSAL:

Dispose of in accordance with local, regional, national, international regulations as specified. Read SDS for detailed product information. SDS may be obtained by calling (866) 819-6825.

SUPPLEMENTAL INFORMATION:

Shelf Life: 2 years from date of manufacture in unopened, properly stored container. Avoid excessive heat or cold. Protect from freezing. Store indoors at a temperature of 65°-95°F.

Disclaimer: Users should determine the suitability of this information or product for their own particular purpose or application. Manufacturer is not responsible for the misuse of this product. This Technical Data sheet and the information conveyed herein supersede all previous versions.

Revision date: July 10, 2020.

FloorScore is a registered trademark of The Resilient FloorCovering Institute.
EcoPure is a registered trademark of Bio-Tec Environmental.



Karndean
Designflooring

1100 Pontiac Court
Export, PA 15632
888-266-4343

www.karndean.com