



Technical Data



	Standard	Result	Product	Size (mm)
		See separate table	RKP8101	1420 x 225
	ISO 24346	6.5 mm	RKP8103	1420 x 225
		5G® Fold Down installation system	RKP8104	1420 x 225
	ISO 24340	0.5 mm	RKP8105	1420 x 225
		K-Guard+ PU coating	RKP8106	1420 x 225
	Commercial	15 year wear**	RKP8108	1420 x 225
	Domestic	Lifetime wear**	RKP8112	1420 x 225
		Micro	RKP8116	1420 x 225
	EN 16511	Pass: Multilayer modular floorcovering panels	RKP8118	1420 x 225
	ISO 10874 Commercial	33: Commercial heavy	RKP8119	1420 x 225
	ISO 10874 Domestic	23: Domestic heavy	RKP8120	1420 x 225
	AS ISO 9239.1 2003	CRF: Smoke value: 6.8 kW/m ² 154 % min	RKP8121	1420 x 225
	EN 438-2	Pass (grade 5)	RKP8203	1420 x 225
	EN ISO 105-B02	Pass ≥6	RKP8205	1420 x 225
	EN13329 Annex E	Pass 4000 cycles	RKP8207	1420 x 225
	EN 424	Pass (no visible damage)	RKP8208	1420 x 225
	BS EN ISO 23999	Pass ≤0.25%	RKP8210	1420 x 225
	ISO 24336	Pass (0.2 %)	RKP8213	1420 x 225
	EN ISO 10140-1:2016 and EN ISO 10140-3:2010+A1:2015 NCC F5.3(a) requirement of ≤ 62 dB under ISO 717.2:2013 G6.3.2 impact insulation class ≥55 IIC ASTM E492-09	ΔL _w = 21 dB Ln,w = 52 dB Pass IIC 62	RKP8216	1420 x 225
		Suitable for use on upper floors of residential high rise apartment buildings without the need for a separate acoustic underlay	RKT2409	457 x 600
	ISO 24343-1	≤0.1 mm	RKT2410	457 x 600
	EN13329 Annex F	Pass ≥1800 mm	RKT2411	457 x 600
	ISO 4918/ EN 425	Pass 25 000 cycles	RKT2412	457 x 600
	ISO 8302	0.0515 m ² K/W Suitable for underfloor heating max 27 °C	RKT2413	457 x 600
	AS4586:2013 Appendix D	R10	RKT2414	457 x 600
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.	RKT2415	457 x 600
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.	RKT3006-G	457 x 600
	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)	RKT3014-G	457 x 600
	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Silver certified product	RKT3015-G	457 x 600
		None required; please install according to our installation instructions.	RKT3016-G	457 x 600
		Suitable	RKT3017-G	457 x 600
		Yes		

*5G® is a patented technology invented by Välinge Innovation AB. The 5G® word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

**Subject to terms

***Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia
Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndean.com

New Zealand
Call: 0800 44 21 01
Email: customerservice@karndean.co.nz
Visit: www.karndean.com

