












	Standard	Result
 Size	DIN EN 16354:2019-01	Length: 8000 mm Width: 1000 mm (± 1,00 mm)
 Thickness	DIN EN 16354:2019-01	- 2,0 mm (± 0,15 mm)
 Mass per unit area		- 2,00 kg/m ² (± 0,15 kg/m ²)
Guarantee ¹		See specific Karndean range
 Reflected walking sound		up to 7 %
 Acoustic impact noise reduction ²	DIN EN 16251-1	- 15 dB
 Indentation - residual	DIN EN 16354:2019-01	0,01 m ² K/W (- 0,1 TOG)
 Thermal resistance	DIN EN ISO 24343-1	< 0,34 mm
 Compressive strength	acc. to DIN EN 826 (250 Pa, 0,5 mm)	> 45 t/m ² (> 450 kPa)
Compressive creep	DIN EN 16354:2019-01	> 50 kPa
 Dynamic load	DIN EN 16354:2019-01	> 3 000 000 cycles
Resistance to large ball	DIN EN 16354:2019-01	- 800 mm
Punctual conformability	DIN EN 16354:2019-01	- 0,79 mm
 Reaction to fire	DIN EN 13501-1	B _{f1} -s1
 Phthalate Free		Yes
Free from plasticizers, asbestos, formaldehyde, halogens and heavy metals		Yes

¹ We do not recommend this underlay be installed with other brands of floorcoverings, please contact customer services for further information. Underlay does not include an industrial guarantee for any range.

² Combined results with LVT adhered

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com

Feb 22



<https://www.blauer-engel.de/uz156>