

	Standard	Result
Size	ISO 24342	1219.2 mm x 177.8 mm
Thickness	ISO 24346	3.0 mm
Wear layer	ISO 24340	0.5 mm
Surface treatment		K-Guard+ PU coating
Warranty <sup>1</sup>	Commercial	15 years wear
	Domestic	Lifetime wear
Bevelled edge		Micro
Standards	ASTM F1700	Pass
Classification	ISO 10874 - Commercial	33: Commercial heavy
	ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	AS/NZS 9239.1:2010	CRF: 7.3 kW/m <sup>2</sup> Smoke value: 124% min.
Staining resistance	EN ISO 26987/EN 423	Excellent
	ASTM F925	Pass
Light fastness	ISO 105-B02	Pass (≥ 7)
	ASTM F1515	Pass (< 8)
Abrasion resistance	EN 660-2	Group T
	ISO 10582	Type 1
	ASTM D3884	Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ISO 23999	Pass (≤ 0.25%)
	ASTM F2199	Pass
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 4 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ISO 24343-1	Pass (≤ 0.1 mm)
	ASTM F1914	Pass (< 8%)
Castor chair continuous use	EN 425	Pass
Thermal resistance	ISO 8302	0.0118 m <sup>2</sup> /K/W Suitable for underfloor heating. Max 27°C
Slip resistance <sup>2</sup>	AS/NZS 4586:2013	R10
Adhesive	General use:	Karndean Mega-Bond
	High temperature:	Karndean 8000 2-part Polyurethane
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level A; LCA Silver Plus;
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.
	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)
	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Conformant product
Recycling		Suitable
Phthalate free		Yes

<sup>1</sup> Subject to terms. Please see our website.

<sup>2</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

**For more information:**

**Australia**

Call: 1800 33 11 70  
Email: customerservice@karndean.com.au  
Visit: www.karndean.com

**New Zealand**

Call: 0800 44 21 01  
Email: customerservice@karndean.co.nz  
Visit: www.karndean.com

Mar 22





Product Code	Size		Box Quantity		Slip Resistance Oil-Wet Ramp
	mm	inches	m <sup>2</sup>	Pieces	
VGW81T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW82T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW84T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW85T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW86T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW89T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW103T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW107T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW110T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW111T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW112T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW127T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW128T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW129T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW130T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW131T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW132T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW133T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW134T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10
VGW135T	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10

Wood Designs