

	Standard	Result
Size	ISO 24342	See separate table
Thickness	ISO 24346	2.0 mm
Wear layer	ISO 24340	0.3 mm
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial	10 years light commercial wear
	Domestic	Lifetime wear
Bevelled edge		No
Standards	EN 649/EN ISO 10582	Pass
	ASTM F1700	Pass
Classification	ISO 10874 - Commercial	31: Commercial moderate
	ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	AS/NZS ISO 9239.1:2010	CRF: 8.1 kW/m ² Smoke value: 42% min.
Staining resistance	EN ISO 26987/EN 423	Excellent
	ASTM F925	Pass
Light fastness	ISO 105-B02	Pass (≥ 6)
	ASTM F1515	Pass (< 8)
Abrasion resistance	EN 660-2	Group T
	ISO 10582	Type 1
	ASTM D3884	Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ISO 23999	Pass (≤ 0.25%)
	ASTM F2199	Pass
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 1 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ISO 24343-1	Pass (≤ 0.1 mm)
	ASTM F1914	Pass (< 8%)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0100 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ²	AS/NZS 4586:2013	See separate table
Adhesive	General use:	Karndean Mega-Bond
	High temperature:	Karndean 8000 2-part Polyurethane
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level 'A' + LCA Rate 'Silver Streamlined'
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.
	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)
	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Conformant product
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia


Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01
Email: customerservice@karndean.co.nz
Visit: www.karndean.com

Mar 22





	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	Oil-Wet Ramp
Wood Designs	KP94-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP95-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP96-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP99-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP104-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP105-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP138-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP141-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP143-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP144-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP146-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP147-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP149-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP150-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
	KP153-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10
KP157-7	1219.2 x 177.8	48" x 7"	4.335	20 Planks	R10	
Stone Designs	ST16	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST17	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST19	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST20	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST21	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9
	ST22	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R9