
























	Standard	Result
 Size	ISO 24342	See separate table
 Thickness	ISO 24346	4.5 mm
 Wear layer	ISO 24340	0.3 mm
Locking system¹		2G™ angling installation system
Surface treatment		K-Guard+ PU coating
Warranty²	Commercial Domestic	10 years wear Lifetime wear
 Bevelled edge		No
 Standards	EN 16511	Pass: Multilayer modular floorcovering panels
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	31: Commercial moderate 23: Domestic heavy
 Reaction to fire	AS ISO 9239.1:2003	CRF: 10.1 kW/m ² Smoke value: 171% min.
 Staining	EN 438-2	Pass (Grade 5)
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN 13329 Annex E	Pass (> 10 000 cycles)
 Furniture chair leg	EN 424	Pass (No visible damage)
 Dimensional stability	BS EN ISO 23999	Pass (≤ 0.25%)
 Swelling	ISO 24336	Pass (0.2%)
 Acoustic impact noise reduction	EN ISO 10140-1:2016	ΔL _w = 19 dB
 Indentation - residual	ISO 24343-1	Pass (≤ 0.1 mm)
 Impact resistance	EN 13329 Annex F	Pass (≥ 1800 mm)
 Castor chair continuous use	EN 425/ISO 4918	Pass (10 000 cycles)
 Thermal resistance	ISO 8302	0.0338 m ² K/W Suitable for underfloor heating. Max 27°C
 Slip resistance³	AS4586:2013 Appendix D	See separate table
 Adhesive		None required; please install according to our installation instructions.
 Environmental	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
 Recycling		Suitable
 Phthalate free		Yes

¹ 2G™ is a patented technology invented by Välinge Innovation AB. The 2G™ word mark and logo are registered trademarks owned by Välinge Innovation AB and any use of such marks is under license.

² Subject to terms. Please see our website.

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia

Call: 1800 33 11 70

Email: customerservice@karndean.com.au

Visit: www.karndean.com

New Zealand


Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.com

Mar 22





Product Code	Size		Box Quantity		Slip Resistance Oil-Wet Ramp	
	mm	inches	m ²	Pieces		
Wood Designs	SCB-KP94	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP95	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP96	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP99	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP104	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP105	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP138	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP141	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP143	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP144	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP146	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP147	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP149	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP150	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
	SCB-KP153	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10
SCB-KP157	1220.0 x 180.0	48.03" x 7.09"	3.074	14 Planks	R10	
Stone Designs	SCB-ST16-18	304.8 x 457.2	12" x 18"	2.787	20 Tiles	R9
	SCB-ST17-18	304.8 x 457.2	12" x 18"	2.787	20 Tiles	R9
	SCB-ST19-18	304.8 x 457.2	12" x 18"	2.787	20 Tiles	R9
	SCB-ST20-18	304.8 x 457.2	12" x 18"	2.787	20 Tiles	R9
	SCB-ST21-18	304.8 x 457.2	12" x 18"	2.787	20 Tiles	R9
	SCB-ST22-18	304.8 x 457.2	12" x 18"	2.787	20 Tiles	R9