






















	Standard	Result
 Size	ISO 24342	1500.0 mm x 250.0 mm
 Thickness	ISO 24346	4.5 mm
 Wear layer	ISO 24340	0.5 mm
Surface treatment		K-Guard+ PU coating
Backing		PVC Friction Pad
Warranty ¹	Commercial Residential	15 years wear Lifetime wear
 Bevelled edge		No
 Standards	ASTM F1700	Pass
 Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
 Reaction to fire	AS/NZS ISO 9239.1:2003	CRF: 8.3 kW/m ² Smoke Value: 143% min.
 Staining resistance	EN ISO 26987/EN 423 ASTM F925	Excellent Pass
 Light fastness	ISO 105-B02 ASTM F1515	Pass (≥ 7) Pass (< 8)
 Abrasion resistance	EN 649 ISO 10582 ASTM D3884	Group T Type 1 Pass
 Flexibility	ISO 24344	Pass
 Dimensional stability	EN 434/ISO 23999 ASTM F2199	Pass (≤ 0.10%) Pass
 Acoustic impact noise reduction	ISO 140-8 Improved Impact Sound Insulation ASTM E492-09 Impact Insulation Class	ΔL _w = 14 dB IIC 56 dB Suitable for use on upper floors of residential high-rise apartment buildings without the need for a separate acoustic underlay under certain build specifications - precise details available from Karndeans. NCC 2016 F5.3 (a) result refers to Karndeans INSUL Marshall Day Software report for your MULTI Res specification including AAAC Star rating
 Electrical behaviour body voltage	EN 1815 AATCC 134-1996	Pass Pass
 Indentation - residual	EN 433/ISO 24343-1 ASTM F1914	Pass (≤ 0.1 mm) Pass (< 8%)
 Castor chair continuous use	EN 425/ISO 4918	Pass
 Thermal resistance	ISO 8302	0.0245 m ² /K/W Suitable for underfloor heating. Max 27°C
 Slip resistance ²	AS/NZS 4586:2013	R10
 Adhesive		Karndeans Hi-Tack PS Adhesive when applicable; please refer to our installation instructions.
Environmental	GBCA/NZGBC GreenStar Rating System Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332	GreenTag Level 'A'; LCA Silver Plus; Best Practice PVC Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Silver certified product
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia

Call: 1800 33 11 70
Email: customerservice@karndeans.com.au
Visit: www.karndeans.com

New Zealand

Call: 0800 44 21 01
Email: customerservice@karndeans.co.nz
Visit: www.karndeans.com

Mar 22



Product Code	Size		Box Quantity		Slip Resistance
	mm	inches	m ²	Pieces	Oil-Wet Ramp
LLP301	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP302	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP304	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP306	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP308	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP310	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP311	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP312	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP313	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP314	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP316	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP317	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP325	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP326	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP327	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP328	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP329	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP331	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP334	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10
LLP335	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10

Wood Designs