
























|  | Standard                           | Result  |
|--|------------------------------------|---|
|  <b>Size</b>  | ISO 24342                          | See separate table  |
|  <b>Thickness</b>                                   | ISO 24346                          | 2.5 mm  |
|  <b>Wear layer</b>                                  | ISO 24340                          | 0.5 mm  |
| <b>Surface treatment</b>   |                                    | K-Guard+ PU coating   |
| <b>Warranty<sup>1</sup></b>  | Commercial                         | 15 years wear   |
|  | Domestic                           | Lifetime wear   |
|  <b>Bevelled edge</b>                               |                                    | Micro   |
|  <b>Standards</b>                                   | ASTM F1700                         | Pass  |
|  <b>Classification</b>                              | ISO 10874 - Commercial             | 33: Commercial heavy  |
|  | ISO 10874 - Domestic               | 23: Domestic heavy  |
|  <b>Reaction to fire</b>                            | AS/NZS 9239.1:2010                 | CRF: > 11 kW/m <sup>2</sup><br>Smoke value: 93% min.                            |
|  <b>Staining resistance</b>                         | EN ISO 26987/EN 423                | Excellent   |
|  <b>Light fastness</b>                              | ASTM F925                          | Pass  |
|  | ISO 105-B02                        | Pass (≥ 7)  |
|  | ASTM F1515                         | Pass (< 8)  |
|  <b>Abrasion resistance</b>                         | EN 660-2                           | Group T   |
|  | ISO 10582                          | Type 1  |
|  | ASTM D3884                         | Pass  |
|  <b>Flexibility</b>                                 | ISO 24344                          | Pass  |
|  <b>Dimensional stability</b>                       | EN 434/ISO 23999                   | Pass (≤ 0.25%)  |
|  | ASTM F2199                         | Pass  |
|  <b>Acoustic impact noise reduction<sup>2</sup></b> | EN ISO 717-2/EN ISO 140-8          | ΔL <sub>w</sub> = 2 dB  |
|  <b>Electrical behaviour body voltage</b>          | EN 1815                            | Pass  |
|  <b>Indentation - residual</b>                    | EN 433/ISO 24343-1                 | Pass (≤ 0.1 mm)   |
|  | ASTM F1914                         | Pass (< 8%)   |
|  <b>Castor chair continuous use</b>               | EN 425/ISO 4918                    | Pass  |
|  <b>Thermal resistance</b>                        | ISO 8302                           | 0.0097 m <sup>2</sup> K/W<br>Suitable for underfloor heating. Max 27°C          |
|  <b>Slip resistance<sup>3</sup></b>               | AS/NZS 4586:2013                   | See separate table  |
|  <b>Adhesive</b>                                  | General use:                       | Karndean Mega-Bond  |
|  | High temperature:                  | Karndean 8000 2-part Polyurethane   |
| <b>Environmental</b>   | GBCA/NZGBC GreenStar Rating System | GreenTag Level A;<br>LCA Silver Plus; Best Practice PVC                         |
|  | Floorscore SCS-EC10.3-2014 v4.0    | Indoor air quality certified;<br>Compliant low emitting VOC emissions.          |
|  <b>Indoor Air Comfort</b>                        | Indoor Air Comfort                 | Gold certification<br>Compliant low emitting VOC emissions.                     |
|  <b>EPD</b>                                       | Environmental Product Declaration  | Product-specific Type III EPD (products with external third-party verification) |
|  | NSF/ANSI 332                       | Sustainability Assessment for Resilient Floor Coverings;<br>Conformant product  |
|  <b>Recycling</b>                                 |                                    | Suitable  |
|  <b>Phthalate free</b>                            |                                    | Yes   |

<sup>1</sup> Subject to terms. Please see our website.

<sup>2</sup> Result is Ln,w = 58 dB when installed on Regupal 4515 acoustic underlay

<sup>3</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

**For more information:**

**Australia**


Call: 1800 33 11 70  
Email: customerservice@karndean.com.au  
Visit: www.karndean.com

**New Zealand**

Call: 0800 44 21 01  
Email: customerservice@karndean.co.nz  
Visit: www.karndean.com

Mar 22





|               | Product Code | Size           |           | Box Quantity   |           | Slip Resistance<br>Oil-Wet Ramp |
|---------------|--------------|----------------|-----------|----------------|-----------|---------------------------------|
|               |              | mm             | inches    | m <sup>2</sup> | Pieces    |                                 |
| Wood Designs  | WP311        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP312        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP313        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP315        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP316        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP318        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP319        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP329        | 914.4 x 152.4  | 36" x 6"  | 3.345          | 24 Planks | R10                             |
|               | WP411        | 1219.2 x 228.6 | 48" x 9"  | 3.345          | 12 Planks | R10                             |
|               | WP411-SRA    | 1219.2 x 228.6 | 48" x 9"  | 3.345          | 12 Planks | R11                             |
|               | WP413        | 1219.2 x 228.6 | 48" x 9"  | 3.345          | 12 Planks | R10                             |
|               | WP414        | 1219.2 x 228.6 | 48" x 9"  | 3.345          | 12 Planks | R10                             |
|               | WP421        | 1219.2 x 228.6 | 48" x 9"  | 3.345          | 12 Planks | R10                             |
| Stone Designs | SP111        | 457.2 x 457.2  | 18" x 18" | 3.345          | 16 Tiles  | R10                             |
|               | SP114        | 457.2 x 457.2  | 18" x 18" | 3.345          | 16 Tiles  | R10                             |
|               | SP115        | 457.2 x 457.2  | 18" x 18" | 3.345          | 16 Tiles  | R10                             |
|               | SP211        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP212        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP213        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP213-SR     | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP214        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP215        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP216        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |
|               | SP217        | 457.2 x 609.6  | 18" x 24" | 3.345          | 12 Tiles  | R10                             |