

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2.5 mm
Wear layer	EN ISO 24340	0.55 mm
Surface treatment		K-Guard+ PU coating
Guarantee ¹	Light industrial Commercial Residential	15 years 15 years Lifetime guarantee
Bevelled edge		Micro
Mass per unit area	EN ISO 23997	4398 g/m ²
Standards	EN 649/EN ISO 10582	Pass
Classification	EN 685/EN ISO 10874 - Light industrial EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 649 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0097 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ²	EN 13893 DIN 51130	DS R10
Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
Adhesive	Karndean Universal Acrylic Epoxy High Temperature+ Pressure Sensitive	Yes Yes Yes Yes Yes
Environmental	Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration NSF/ANSI 332	Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Sustainability Assessment for Resilient Floor Coverings; Conformant product
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.


For more information:
UK: 01386 820104 | ROI: 01 6569887
Email: commercial@karndean.co.uk
Visit: www.karndean.com



May 21



EN 14041:2004 (DOP 2017/OP/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/33/42 Manufactured to ISO 10582



	Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	WP311	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	35
	WP313	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	16
	WP314	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	32
	WP318	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	6
	WP411	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	30
	WP412	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	26
	WP413	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	26
	WP414	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	10
	WP418	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	27
	WP419	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	44
	WP422	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	47
	WP423	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	33
	REN113	914.4 x 101.6	36" x 4"	3.345	36 Planks	R10	27
Stone Designs	SM-SP216	76.2 x 457.2	3" x 18"	3.345	96 Tiles	R10	23
	SM-SP217	76.2 x 457.2	3" x 18"	3.345	96 Tiles	R10	35
	SM-SP221	177.8 x 711.2	7" x 28"	3.288	26 Tiles	R10	71
	SP111	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10	66
	SP112	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10	61
	SP114	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10	10
	SP115	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10	8
	SP211	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	45
	SP212	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	45
	SP213	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	23
	SP214	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	16
	SP215	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	13
	SP216	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	23
	SP217	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	35
	SP218	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	9
SP221	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	71	