

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	3.0 mm
Wear layer	EN ISO 24340	0.7 mm
Surface treatment		K-Guard+ PU coating
Guarantee ¹	Light industrial	20 years
	Commercial	20 years
	Residential	Lifetime guarantee
Bevelled edge		Standard
Mass per unit area	EN ISO 23997	5015 g/m ²
Standards	EN 649/EN ISO 10582	Pass
Classification	EN 685/EN ISO 10874 - Light industrial	43: Light industrial heavy
	EN 685/EN ISO 10874 - Commercial	34: Commercial very heavy
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 649	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0147 m ² K/W
		Suitable for underfloor heating. Max 27°C
Slip resistance ²	EN 13893	D5
	DIN 51130	See separate table
Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
Adhesive	Karndean Universal	Yes
	Acrylic	Yes
	Epoxy	Yes
	High Temperature+	Yes
	Pressure Sensitive	Yes
Environmental	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions
EPD	Environmental Product Declaration NSF/ANSI 332	External third-party verified Type III EPD Sustainability Assessment for Resilient Floor Coverings; Conformant product
Recycling		Suitable
Pthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887
 Email: commercial@karndean.co.uk
 Visit: www.karndean.com



May 21



EN 14041: 2004 (DOP 2017/AS/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/34/43 Manufactured to ISO 10582

	Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	AP01	228.6 x 76.2	9" x 3"	3.345	192 Planks	R10	27
	AP02	228.6 x 76.2	9" x 3"	3.345	192 Planks	R10	14
	AP03	228.6 x 76.2	9" x 3"	3.345	192 Planks	R10	6
	AP07	228.6 x 76.2	9" x 3"	3.345	192 Planks	R10	27
	EW01	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	14
	EW02	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	9
	EW03	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	12
	EW10	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R10	36
	EW11	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R10	33
	EW12	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R10	25
	EW13	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R10	33
	EW21	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R11	15
	HC01	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	14
	HC02	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	16
	HC03	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	17
	HC04	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	10
	HC05	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	8
	HC06	914.4 x 152.4	36" 6"	3.345	24 Planks	R10	6
	RL01	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10	27
	RL02	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10	20
	RL03	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10	14
	RL04	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10	8
	RL12	1219.2 x 177.8	48" x 7"	3.252	15 Planks	R10	27
	RL20	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R11	29
	RL21	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R11	41
	RL22	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R11	41
	RL23	1422.4 x 228.6	56" x 9"	3.252	10 Planks	R11	41
	RPL-EW21	114.3/152.4/228.6 widths Various lengths	4.5"/6"/9" widths Various lengths	3.902	27 Planks	R11	15
	SM-RL20	457.2 x 76.2	18" x 3"	3.345	96 Planks	R11	29
	SM-RL21	457.2 x 76.2	18" x 3"	3.345	96 Planks	R11	41
SM-RL22	457.2 x 76.2	18" x 3"	3.345	96 Planks	R11	41	
SM-RL23	457.2 x 76.2	18" x 3"	3.345	96 Planks	R11	41	
Stone Designs	LM01	Panel of assorted tiles with design strips ³ : 457.2 x 457.2 304.8 x 457.2 152.4 x 457.2 304.8 x 304.8 152.4 x 304.8 152.4 x 152.4	Panel of assorted tiles with design strips ³ : 18" x 18" 12" x 18" 6" x 18" 12" x 12" 6" x 12" 6" x 6"	3.720	4 Panels	R10	49
	LM02			3.720	4 Panels	R10	35
	LM03			3.720	4 Panels	R10	59
	LM10			3.720	4 Panels	R10	10
	LM11			3.720	4 Panels	R10	17
	LM12			3.720	4 Panels	R10	21
	LM20			3.720	4 Panels	R10	13
	LM05			457.2 x 609.6	18" x 24"	3.345	12 Tiles
	LM06	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	10
	LM07	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	49
	LM08	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	31
	LM09	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	42
	LM15	406.4 x 406.4	16" x 16"	3.303	20 Tiles	R10	19
	LM15-CLIP	406.4 x 406.4	16" x 16"	3.303	20 Tiles	R10	19
	LM16	406.4 x 406.4	16" x 16"	3.303	20 Tiles	R10	61
	LM16-CLIP	406.4 x 406.4	16" x 16"	3.303	20 Tiles	R10	61
	LM21	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	21
	LM22	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10	17
	LM27	152.4 x 914.4	6" x 36"	3.345	24 Tiles	R10	49
	LM28	152.4 x 914.4	6" x 36"	3.345	24 Tiles	R10	31
LM29	152.4 x 914.4	6" x 36"	3.345	24 Tiles	R10	42	

³ Offsetting tiles to create a natural look