

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	2.0 mm
Wear layer	EN ISO 24340	0.3 mm
Surface treatment		K-Guard+ PU coating
Guarantee ¹	Commercial Residential	10 years Lifetime guarantee
Bevelled edge		No
Mass per unit area	EN ISO 23997	3605 g/m ²
Standards	EN 649/EN ISO 10582	Pass
Classification	EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	31: Commercial moderate 23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 649/EN ISO 10582 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 1 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0084 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ²	EN 13893 DIN 51130	DS R10
Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
Adhesive	Karndean Universal Acrylic Epoxy High Temperature+ Pressure Sensitive	Yes Yes Yes Yes Yes
Environmental	Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration NSF/ANSI 332	Gold certification; Compliant low emitting VOC emissions. Indoor air quality certified; Compliant low emitting VOC emissions. External third-party verified Type III EPD Sustainability Assessment for Resilient Floor Coverings; Conformant product
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faible émission) à C (forte émission)

May 21



EN 14041: 2004 (DOP 2017/RLU/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/31
Manufactured to ISO 10582





	Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	KP39	914.4 x 101.6	36" x 4"	3.345	36 Planks	R10	29
	KP40	914.4 x 101.6	36" x 4"	3.345	36 Planks	R10	30
	KP51	914.4 x 101.6	36" x 4"	3.345	36 Planks	R10	36
	KP67	914.4 x 101.6	36" x 4"	3.345	36 Planks	R10	18
	KP91	914.4 x 101.6	36" x 4"	3.345	36 Planks	R10	20
	KP94	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	31
	KP95	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	32
	KP96	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	18
	KP97	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	19
	KP98	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	9
	KP99	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	36
	KP102	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	14
	KP103	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	13
	KP104	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	25
	KP105	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	60
	KP131	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	48
	KP132	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	63
	KP133	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	53
	KP136	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	42
	KP138	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	33
KP141	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10	22	
SM-KP94	457.2 x 76.2	18" x 3"	3.345	96 Planks	R10	31	
SM-KP99	457.2 x 76.2	18" x 3"	3.345	96 Planks	R10	36	
SM-KP132	457.2 x 76.2	18" x 3"	3.345	96 Planks	R10	63	
SM-KP138	457.2 x 76.2	18" x 3"	3.345	96 Planks	R10	33	
Stone Designs	ST5	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	55
	ST8	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	64
	ST10	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	48
	ST11	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	44
	ST12	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	39
	ST13	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	34
	ST14	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	18
	ST15	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	11
	ST16	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	28
	ST17	304.8 x 457.2	12" x 18"	3.345	24 Tiles	R10	63
	T74	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	8
	T88	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	8
	T90	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	55
	T98	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	59
	T100	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	11
T101	304.8 x 304.8	12" x 12"	3.345	36 Tiles	R10	20	