

	Standard	Result
<b>Size</b>	EN ISO 24342	1500.0 mm x 250.0 mm
<b>Thickness</b>	EN ISO 24346	4.5 mm
<b>Wear layer</b>	EN ISO 24340	0.55 mm
<b>Surface treatment</b>		K-Guard+ PU coating
<b>Guarantee<sup>1</sup></b>	Light industrial	15 years
	Commercial	15 years
	Residential	Lifetime guarantee
<b>Bevelled edge</b>		No
<b>Mass per unit area</b>	EN ISO 23997	7470 g/m <sup>2</sup>
<b>Standards</b>	EN 649/EN ISO 10582	Pass
<b>Classification</b>	EN 685/EN ISO 10874 - Light industrial	42: Light industrial general
	EN 685/EN ISO 10874 - Commercial	33: Commercial heavy
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
<b>Reaction to fire</b>	EN 13501-1	B <sub>fl</sub> -s1
<b>Staining resistance</b>	EN ISO 26987/EN 423	Excellent
<b>Light fastness</b>	EN ISO 105-B02	Pass (≥ 7)
<b>Abrasion resistance</b>	EN 649	Group T
	EN ISO 10582	Type 1
<b>Flexibility</b>	EN ISO 24344	Pass
<b>Dimensional stability</b>	EN 434/EN ISO 23999	Pass (≤ 0.10%)
<b>Acoustic impact noise reduction</b>	EN ISO 717-2/EN ISO 140-8	ΔL <sub>w</sub> = 13 dB
<b>Indentation - residual</b>	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
<b>Castor chair continuous use</b>	EN 425/ISO 4918	Pass
<b>Thermal resistance</b>	ISO 8302	0.0245 m <sup>2</sup> K/W
		Suitable for underfloor heating. Max 27°C
<b>Slip resistance<sup>2</sup></b>	EN 13893	DS
	DIN 51130	R10
<b>Light Reflectance Value (LRV)</b>	BS 8493:2008+A1:2010	See separate table
<b>Adhesive</b>		Please install according to our installation instructions.
<b>Environmental</b>	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions
	Environmental Product Declaration	External third-party verified Type III EPD
<b>Recycling</b>		Suitable
<b>Phthalate free</b>		Yes

<sup>1</sup> Subject to terms. Please see our website.

<sup>2</sup> Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com



May 21



EN 14041:2004 (DOP 2017/LLL/EN/02)
Notified body 0493 Floor coverings (internal)
ISO 10874 Class 23/33/42 Manufactured to ISO 10582



Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV
	mm	inches	m <sup>2</sup>	Pieces		
LLP301	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	20
LLP302	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	11
LLP303	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	11
LLP304	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	31
LLP305	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	20
LLP306	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	40
LLP307	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	21
LLP308	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	29
LLP310	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	31
LLP311	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	58
LLP315	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	14
LLP317	1500.0 x 250.0	59.06" x 9.84"	3.000	8 Planks	R10	26

Wood Designs