

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	4.5 mm
Wear layer	EN ISO 24340	0.55 mm
Surface treatment		K-Guard+ PU coating
Guarantee ¹	Light industrial	15 years
	Commercial	15 years
	Residential	Lifetime guarantee
Bevelled edge		No
Mass per unit area	EN ISO 23997	7470 g/m ²
Standards	EN 649/EN ISO 10582	Pass
Classification	EN 685/EN ISO 10874 - Light industrial	42: Light industrial general
	EN 685/EN ISO 10874 - Commercial	33: Commercial heavy
	EN 685/EN ISO 10874 - Domestic	23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 7)
Abrasion resistance	EN 649	Group T
	EN ISO 10582	Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.10%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 13 dB
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0245 m ² K/W
		Suitable for underfloor heating. Max 27°C
Slip resistance ²	EN 13893	DS
	DIN 51130	R10
Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
Adhesive		Please install according to our installation instructions.
Environmental	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions
	Environmental Product Declaration	External third-party verified Type III EPD
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com



May 21



EN 14041:2004 (DOP 2017/LL/EN/02)
Notified body 0493
Floor coverings (internal)
ISO 10874 Class 23/33/42
Manufactured to ISO 10582



Product Code	Size		Box Quantity		Slip Resistance	LRV
	mm	inches	m ²	Pieces	DIN 51130	
LLP92	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	34
LLP93	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	7
LLP94	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	34
LLP95	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	38
LLP96	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	11
LLP97	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	20
LLP99	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	31
LLP101	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	28
LLP102	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	14
LLP103	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	21
LLP104	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	12
LLP105	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	29
LLP106	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	20
LLP108	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	31
LLP109	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	21
LLP110	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	12
LLP111	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	12
LLP112	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	16
LLP113	1050.0 x 250.0	41.34" x 9.84"	3.150	12 Planks	R10	30
LLT200	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	19
LLT201	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	32
LLT202	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	44
LLT203	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	8
LLT204	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	18
LLT205	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	18
LLT206	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	18
LLT207	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	18
LLT212	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	19
LLT214	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	47
LLT215	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	43
LLT216	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	35
LLT217	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	20
LLT218	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	37
LLT219	500.0 x 610.0	19.69" x 24.02"	3.050	10 Tiles	R10	40