

	Standard	Result
Size	EN ISO 24342	See separate table
Thickness	EN ISO 24346	3.0 mm
Wear layer	EN ISO 24340	0.7 mm
Surface treatment		K-Guard+ PU coating
Guarantee ¹	Light industrial Commercial Residential	20 years 20 years Lifetime guarantee
Bevelled edge		Standard
Mass per unit area	EN ISO 23997	5015 g/m ²
Standards	EN 649/EN ISO 10582	Pass
Classification	EN 685/EN ISO 10874 - Light industrial EN 685/EN ISO 10874 - Commercial EN 685/EN ISO 10874 - Domestic	43: Light industrial heavy 34: Commercial very heavy 23: Domestic heavy
Reaction to fire	EN 13501-1	B _{fl} -s1
Staining resistance	EN ISO 26987/EN 423	Excellent
Light fastness	EN ISO 105-B02	Pass (≥ 6)
Abrasion resistance	EN 649 EN ISO 10582	Group T Type 1
Flexibility	EN ISO 24344	Pass
Dimensional stability	EN 434/EN ISO 23999	Pass (≤ 0.25%)
Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/EN ISO 24343-1	Pass (≤ 0.1 mm)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0147 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ²	EN 13893 DIN 51130	DS See separate table
Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
Adhesive	Karndean Universal Silane Pressure Sensitive	Yes Yes Yes
Environmental	Indoor Air Comfort Floorscore SCS-EC10.3-2014 v4.0 Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	Gold certification; Compliant low emitting VOC emissions Indoor air quality certified; Compliant low emitting VOC emissions External third-party verified Type III EPD Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standard
Recycling		Suitable
Pthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01386 820104 | ROI: 01 6569887

Email: commercial@karndean.co.uk

Visit: www.karndean.com

Feb 23

BS EN 14041: 2004 (DOP 2021/UKCA/AS/01)

Approved body 0321
Floor coverings (internal)

ISO 10874 Class 23/34/43
Manufactured to ISO 10582

EN 14041: 2004 (DOP 2017/AS/EN/02)

Notified body 0493
Floor coverings (internal)

ISO 10874 Class 23/34/43
Manufactured to ISO 10582

Product Code	Size		Box Quantity		Slip Resistance	LRV
	mm	inches	m ²	Pieces	DIN 51130	
AP01	228.6 x 76.2	9.0" x 3.0"	3.345	192 Planks	R10	27
AP02	228.6 x 76.2	9.0" x 3.0"	3.345	192 Planks	R10	14
AP03	228.6 x 76.2	9.0" x 3.0"	3.345	192 Planks	R10	6
AP05	228.6 x 76.2	9.0" x 3.0"	3.345	192 Planks	R10	9
AP06	228.6 x 76.2	9.0" x 3.0"	3.345	192 Planks	R10	16
AP07	228.6 x 76.2	9.0" x 3.0"	3.345	192 Planks	R10	27
SBW-RL01	304.8 x 76.2 / 114.3 x 114.3	12.0" x 3.0" / 4.5" x 4.5"	3.484	192 Pieces (96 Squares, 96 Planks)	R10	27
SBW-RL12	304.8 x 76.2 / 114.3 x 114.3	12.0" x 3.0" / 4.5" x 4.5"	3.484	192 Pieces (96 Squares, 96 Planks)	R10	27
EW02	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R10	9
EW03	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R10	12
EW10	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R10	36
EW11	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R10	33
EW12	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R10	25
EW13	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R10	33
EW21	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R11	15
HC01	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R10	14
HC02	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R10	16
HC03	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R10	17
HC06	914.4 x 152.4	36.0" x 6.0"	3.345	24 Planks	R10	6
RL01	1219.2 x 177.8	48.0" x 7.0"	3.252	15 Planks	R10	27
RL02	1219.2 x 177.8	48.0" x 7.0"	3.252	15 Planks	R10	20
RL04	1219.2 x 177.8	48.0" x 7.0"	3.252	15 Planks	R10	8
RL05	1219.2 x 177.8	48.0" x 7.0"	3.252	15 Planks	R10	9
RL12	1219.2 x 177.8	48.0" x 7.0"	3.252	15 Planks	R10	27
RL20	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R11	29
RL21	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R11	41
RL22	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R11	41
RL23	1422.4 x 228.6	56.0" x 9.0"	3.252	10 Planks	R11	41
RPL-EW21	114.3/152.4/228.6 widths Various lengths	4.5"/6.0"/9.0" widths Various lengths	3.902	27 Planks	R11	15
SM-RL20	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R11	29
SM-RL21	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R11	41
SM-RL22	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R11	41
SM-RL23	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R11	41

Wood Designs

Product Code	Size		Box Quantity		Slip Resistance DIN 51130	LRV		
	mm	inches	m ²	Pieces				
LM01	Panel of assorted tiles with design strips ¹ : 457.2 x 457.2 304.8 x 457.2 152.4 x 457.2 304.8 x 304.8 152.4 x 304.8 152.4 x 152.4	Panel of assorted tiles with design strips ¹ : 18.0" x 18.0" 12.0" x 18.0" 6.0" x 18.0" 12.0" x 12.0" 6.0" x 12.0" 6.0" x 6.0"	3.720	4 Panels	R10	49		
LM02			3.720	4 Panels	R10	35		
LM03			3.720	4 Panels	R10	59		
LM10			3.720	4 Panels	R10	10		
LM11			3.720	4 Panels	R10	17		
LM12			3.720	4 Panels	R10	21		
LM20			3.720	4 Panels	R10	13		
LM05			457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	18
LM06			457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	10
LM07			457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	49
LM08			457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	31
LM09			457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	42
LM15	406.4 x 406.4	16.0" x 16.0"	3.303	20 Tiles	R10	19		
LM15-CLIP	406.4 x 406.4	16.0" x 16.0"	3.303	20 Tiles	R10	19		
LM16	406.4 x 406.4	16.0" x 16.0"	3.303	20 Tiles	R10	61		
LM16-CLIP	406.4 x 406.4	16.0" x 16.0"	3.303	20 Tiles	R10	61		
LM21	457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	21		
LM22	457.2 x 609.6	18.0" x 24.0"	3.345	12 Tiles	R10	17		
LM27	152.4 x 914.4	6.0" x 36.0"	3.345	24 Planks	R10	49		
LM28	152.4 x 914.4	6.0" x 36.0"	3.345	24 Planks	R10	31		
LM29	152.4 x 914.4	6.0" x 36.0"	3.345	24 Planks	R10	42		

Stone Designs

¹ Offsetting tiles to create a natural look